



I BEAMS

Size in inches and width of flange	Wt./Ft.	Thickness of Web, Ins.	Wt./40'
3" X 2.330	5.70	.170	228
2.509	7.50	.349	300
4" X 2.663	7.70	.193	308
2.796	9.50	.326	380
5" X 3.004	10.00	.214	400
		Wt./20'	
6" X 3.332	12.50	.232	500
3.565	17.25	.465	690
7" X 3.362	15.30	.252	612
8" X 4.001	18.40	.271	736
4.101	23.00	.441	920
10" X 4.661	25.40	.311	1016
4.994	35.00	.594	1400
12" X 5.000	31.80	.350	1272
5.078	35.00	.428	1400
5.252	40.80	.462	1632
5.477	50.00	.687	2000
15" X 5.501	42.90	.411	1716
5.640	50.00	.550	2000
18" X 6.001	54.7	.461	2188
6.251	70.00	.711	2800

Size in inches and width of flange	Wt./Ft.	Thickness of Web, Ins.	Wt./40'
6.385	75.0	.635	3000
7.060	86.0	.660	3440
7.200	96.0	.800	3840
24" X 7.000	80.0	.500	3200
7.125	90.00	.625	3600
7.245	100.00	.745	4000
7.870	106.0	.620	4240
8.050	121.0	.800	4840

JR. BEAMS

Size	Wt./Ft.
6"	4.4
7"	5.5
8"	6.5
10"	8.0
10"	9.0
12"	11.8
14"	17.2